

ELEVATIONS :						
FINISH FLOOR LEVEL						
DR / WD NO.	D1	D2	D3	D4	D5	D6
DESCRIPTION :	40MM THICK OPENABLE ALUMINUM FRAMED DOOR PANEL	40MM THICK OPENABLE TIMBER FRAMED DOOR PANEL	40MM THICK OPENABLE ALUMINUM FRAMED DOOR PANEL	40MM THICK OPENABLE TIMBER FRAMED DOOR PANEL	40MM THICK OPENABLE TIMBER FRAMED DOOR PANEL	40MM THICK OPENABLE TIMBER FRAMED DOOR PANEL
FRAME :	120MM ALUMINUM FRAME	120MM TIMBERFRAME	120MM FRAME	120MM TIMBERFRAME	120MM TIMBERFRAME	120MM TIMBERFRAME
HARDWARE :	DOOR CLOSER CYLINDRICAL LOCK BUTT HINGE STOPPER HOLDER KICKER	DOOR CLOSER CYLINDRICAL LOCK BUTT HINGE STOPPER HOLDER KICKER	DOOR CLOSER CYLINDRICAL LOCK BUTT HINGE STOPPER HOLDER	DOOR CLOSER CYLINDRICAL LOCK BUTT HINGE STOPPER HOLDER	DOOR HANDLE BUTT HINGE	DOOR CLOSER CYLINDRICAL LOCK BUTT HINGE STOPPER HOLDER
GLAZING :	C-6MM ALL FIXED PANELS TO BE DOUBLE GLAZED	C-6MM ALL FIXED PANELS TO BE DOUBLE GLAZED	C-6MM ALL FIXED PANELS TO BE DOUBLE GLAZED	C-6MM ALL FIXED PANELS TO BE DOUBLE GLAZED	C-6MM ALL FIXED PANELS TO BE DOUBLE GLAZED	C-6MM ALL FIXED PANELS TO BE DOUBLE GLAZED

DOOR SCHEDULE

SCALE 1:50

GENERAL NOTE FOR THE INSTALLATION OF DOORS:

ENSURE THAT ALL OPENING EXTERNAL BUILDING PERIMETER DOORS ARE LOCKABLE.  
 PERIMETER DOORS SHOULD MEET THE FOLLOWING BUILDING STANDARDS:  
 – BE FITTED WITH A QUALITY SINGLE CYLINDER LOCKSET THAT COMPLIES WITH FIRE REGULATIONS.